



PRODUCTS

CONSUMABLES

HOW TO BUY

ABOUT

RESOURCES

CONTACT

M350, H350

Search...

HYDRAULIC AUGER DRIVES

- NC150
- NC200, M200, H200
- NC300, M300, H300
- M350, H350
- HTLS6K
- HTLS10K

DIGGER DERRICK

FOUNDATION / PRESSURE AUGER

GENERAL PURPOSE

TM-48 BELLTEC DIGGER

M350, H350

20-35 GPM 3500 ft/lb

MODEL M-350	ORDER NUMBER 113030
Maximum Output Torque	3000 ft/lb
Recommended Fluid Flow	20-35 gpm
Maximum Pressure-Continuous	3500 psi
Recommended Max Auger Dia-Dirt	36 in
Recommended Max Auger Dia-Rock	36 in

OUTPUT Flow GPM	SPEED Speed RPM	OUTPUT Pressure PSI	TORQUE Torque ft/lb
20	51	2000	2388
24	62	2500	2985
26	67	3000	3582
28	72		
30	77		
35	90		

MODEL H-350	ORDER NUMBER 113016
Maximum Output Torque	3000 ft/lb
Recommended Fluid Flow	15-30 gpm
Maximum Pressure-Continuous	3000 psi
Recommended Max Auger Dia-Dirt	36 in
Recommended Max Auger Dia-Rock	36 in

OUTPUT Flow GPM	SPEED Speed RPM	OUTPUT Pressure PSI	TORQUE Torque ft/lb
20	51	2000	2388
24	62	2500	2985
26	67	3000	3582
28	72		
30	77		
35	90		

CUSTOM TOOLING

We have over 30 years of experience designing and providing custom auger tooling drilling systems around the world. We welcome the opportunity to help you with your next project requiring special applications or design. Belltec products are better by design. Give us the opportunity to help you be more profitable. Call and talk directly with our expert team.