

# TECHNICAL DATA

TAMPER

BT 60, BT 65



**Maximum reliability and longevity**  
All around engine protection




**More transparency**  
Hour counter/tachometer with a service indicator which can be reset



**Simple operation**  
Engine and fuel supply with combined switch

**Shipping dimensions in cub.yd**

<b>BT 60</b>	0.345
<b>BT 65</b>	0.345



**Standard Equipment**

- Engine Protection System
  - Protective engine covering
  - Paper air filter system with two stages
  - Automatic oil level control
  - Dual fuel filter system
- Vibration insulated steering bow
- Self-cleaning air filter housing
- Protective covering
- Single point lifting device
- Recoil starter
- Plastic castor as loading aid
- Infinitely variable frequency
- Combination of engine stop/fuel switch
- h-/ rpm meter
- 3-2-1 Warranty

**Dimensions in inch**

	B	H	L	L1	W
<b>BT 60</b>	13.8	40.6	28.7	13.2	9.1
<b>BT 65</b>	13.8	40.6	28.7	13.2	11.0

**Optional Equipment**

- Transport device with puncture proof wheels
- Tamper foot widths (6.3-13 in)
- Tamper foot extensions
- Special painting
- Tool kit
- Service Kit
- Operator protection contact breaker switch
- TOUGH WARRANTY

**Technical Data**

**Weights**

Operating weight CECE .....	lb	128
Basic weight .....	lb	126

**Dimensions**

Working width (tamper plate) .....	in	11.0	11.0
------------------------------------	----	------	------

**Driving Characteristics**

Working speed max. ....	ft/min	65.6	65.6
Area coverage max. ....	sq.ft/h	2,970.9	3,616.8

**Drive**

Engine manufacturer .....		Honda	Honda
Type .....		GXR 120	GXR 120
Emission stage .....		StageV/CARB P.3	StageV/CARB P.3
Cooling .....		air	air
Number of cylinders .....		1	1
Performance SAE J 1349 .....	kW	2.8	2.8
Performance SAE J 1349 .....	hp	3.8	3.8
Fuel .....		Gasoline	Gasoline
Drive system .....		mech.	mech.
Fuel comsump. aver. during operation .....	gal/h	0.2	0.2

**Exciter system**

Frequency .....	vpm	600.0-708.0	600.0-708.0
Impact force .....	lb	3,372	3,822

**Capacities**

Fuel .....	gal	0.8	0.8
------------	-----	-----	-----

Technical modifications reserved. Machines may be shown with options.

