

EXPRESS PRESSURE WASHER TRAILER

Available in 1,250, 1,025 or 500 Gallon



Built for the heavy duty cleaning jobs with the heat, pressure and capacity that you need.



Gas Powered Washer EXP-500L-S-HOTG

- Honda GX electric start engine
 - 5.5 GPM @ 3,500 PSI

Diesel Powered Washer EXP-500L-S-HOTD

- Kohler electric start engine
 - 5.5 GPM @ 4,000 PSI

Check out these features

- "Algae Resistant" Black Tank
- Pressure-Pro Hot High Pressure Washer
- 180° Swivel Hand Crank Hose Reel
- Supply Hose Wrap
- DOT Approved Trailer
- 6" Channel Iron Trailer Frame
- Tandem Spring Axles w/ Surge Brakes
- 2" Anti-Siphon Fill / Hose Bottom Fill
- Heavy Duty Fenders
- LED Lighting



- Equipment Washdown
- Environmental Cleaning
- Building Cleaning
- Water Blasting

wyliesprayers.com







Pressure-Pro Hot Pressure Washer Features and Specifications

Gasoline Powered Pressure-Pro
Engine....... Honda GX630 24 HP
Pump...... High Performance HP5535
Volume....... 5.5 GPM
Pressure...... 3,500 PSI
Temperature....... Max. 120° Rise

Diesel Powered Pressure-Pro
Engine......Kohler KDW1003 23.4 HP
Pump.....General TSP1821
Volume......5.5 GPM
Pressure.....4,000 PSI
Temperature......Max. 120° Rise

Standard Features

- Steel frame with powder coated finish
- Super efficient insulated schedule 80 coil
- Stainless steel coil wrap, burner hood, control panel
- 15 gallon poly fuel tanks with fuel filters
- Electric start engines w/battery
- Reliable diesel fired Beckett burners
- Adjustable thermostat

- Safety pressure relief valve
- 3VX belt system for balanced power transfer
- Gun/wand assembly with quick connects
- 50' high pressure hose w/quick connects
- Maxi-Flo 20% chemical injector
- 4 color coded quick connect spray nozzles
- Industrial grade engines
- Triplex plunger pumps

Trailer Specifications:	500 Gal.	1,250 Gal.		500 Gal.	1,250 Gal.
Tank	500 Gal	1,250 Gal.	Height	70"	76"
Tank Color	"Alg	ae Resistant" black	Length	210"	264"
Frame	6" channel	7" channel	Width	80"	99"
Axles		. Tandem leaf spring	Wheel Track	70"	87"
TiresS	T225/75D15	ST235/80R16	GVWR	6,000 lb	14,000 lb
Hitch	2 5/16" ba	ll; height adjustable	Brakes	Surge	Electric

